

## Disc technical data

**Axle** Front

**Diameter**  
262 mm

**Overall height (A)**  
47,2 mm

**Centring diameter (B)**  
64,2 mm

**Number of holes (C)**  
5


**Thickness (TH)**  
21 mm

**Minimum thickness**  
19,5 mm

**Tightening torque**   
108 Nm

**Unit per box**  
2

**EANCode**  
8020584225721



## Brand part numbers

**Brembo**  
09.5457.3X

**AP**  
25055 X

<b>09.5457.3X</b>	
AP	25055 X
DIMENSION	262 x 21 mm
MIN TH	19.5 mm
BALANCING	GUARANTEED
MATERIAL	SUB-GROUP 2
WEIGHT	5 kg
E11	90R 02C01203/28496
	INSIDE THE BOX 205.5886.21
HC	
	09.5457.3X

DATE : 09/12/2016 VERSION : 00

## Technical specifications

### High Carbon disc (HC)

Thanks to the high percentage of carbon in the chemical composition of the cast iron, the HC disc provides greater damping coefficient, able to reduce vibration and noise while driving.



### Disc with fixing screw

By supplying the fixing screw in the disc box, Brembo provides extra help to the mechanic if the original screw is rusty or worn to such an extent as to prevent or make it difficult to reuse.



### UV Disc

The UV coating process provides a superior corrosion resistance and full disc protection.



## Compatible vehicles

### HONDA

Model	Type	Kw	Year
CIVIC VII Hatchback (EU, EP, EV)	1.4 i	55	02/01 09/05
CIVIC VII Hatchback (EU, EP, EV)	1.4 iS (EP1)	66	02/01 09/05
CIVIC VII Hatchback (EU, EP, EV)	1.6 i	81	02/01 09/05
CIVIC VIII Saloon (FD, FA)	1.3	85	02/06 -

CIVIC VIII Saloon (FD, FA)	1.3 Hybrid (FA3, FD3)	70	01/06 -
CIVIC VIII Saloon (FD, FA)	1.3 Hybrid (FD3)	85	01/10 02/12
CIVIC VIII Saloon (FD, FA)	1.6	84	09/05 -
CIVIC VIII Saloon (FD, FA)	1.8 (FD1, FD7)	103	09/05 02/12
CR-Z (ZF)	1.5 Hybrid	91	09/10 12/13
CR-Z (ZF)	1.5 Hybrid	97	09/13 -
CR-Z (ZF)	1.5 Hybrid	89	11/12 -
CR-Z (ZF)	1.5 Hybrid (ZF1)	84	06/10 -
<b>HONDA (DONGFENG)</b>			
Model	Type	Kw	Year
CIIMO	1.8	103	04/12 -

## OE Part number

Compatible OE codes	
HONDA	45251S6M000
HONDA	45251SNA000
HONDA	45251SNA010
HONDA	45251SZT020
HONDA	45251SZT030
HONDA	45251SZT040